



Collection	Composition	Weight / Thickness	Abrasion	
Harbor	Polycarbonate Blended Surface	12.53 oz. per sq. yard Approx. 0.95 mm	ASTM D4157 / 200,000 DR Wyzenbeek	
	65% Polyester, 35% Cotton Backing			
Bayside	Polycarbonate Blended Surface	12.53 oz. per sq. yard Approx. 0.95 mm	ASTM D4157 / 200,000 DR Wyzenbeek	
	65% Polyester, 35% Cotton Backing			
Width:	54"			
Hydrolysis:	10 Weeks ASTM D3690 SECT. 6.11 (Hydrolytic Stability) / ISO 1419 Method C (Accelerated Ageing)			
F/R Rating:	ASTM E84 (adhered) - Class A CA TB 117 - Pass	·	cifications. These fabrics, when treated le furniture components, have been	
	FMVSS 302 & 95/28 ANNEX IV - Pass		test conditions BS 5852 Source 0, 1 & 5	
	NFPA 260 - Class 1 UFAC - Class 1	(Cig, Match and Crib 5), BS EN 10 (Bayside Only)	(Cig, Match and Crib 5), BS EN 1021 Part 1 & 2 (Cig & Match). (Bayside Only)	
Adhesion of Coating:	ASTM D751			
Tear Strength:	ASTM D2261			
Breaking Strength:	ASTM D5034			
Tensile Strength:	BS EN ISO 1421			
Colorfastness to Crocking	: AATCC 8, Grade 4-5 Wet & Dry			
Colorfastness to Light:	AATCC 16.3, 200 Hours, Grade 4 ISO 105 B02, Grade 6			

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website – www.paulbraytondesigns.com

